

ANCHORLIFT[®]

WORLD CLASS WINDLASS SYSTEM

HIGHSPEED
WINDLASS

Barracuda 600

Boats from 20ft to 30ft 4000kg / 8800Lbs.



Model No:

- BA612-6** Barracuda Aluminium Low profile. Chain: 6mm DIN766 Rope: 12 and 14mm
- BA612-7** Barracuda Aluminium Low profile. Chain: 1/4"HT G43, 7mm DIN766 Rope: 1/2", 12 and 14mm
- BA612C-6** Barracuda Aluminium w/capstan. Chain: 6mm DIN766 Rope: 12 and 14mm
- BA612C-7** Barracuda Aluminium w/capstan. Chain: 1/4"HT G43, 7mm DIN766 Rope: 1/2", 12 and 14mm
- B612-6** Barracuda Stainless S. Low profile. Chain: 6mm DIN766 Rope: 12 and 14mm
- B612-7** Barracuda Stainless S. Low profile. Chain: 1/4"HT G43 / 7mm DIN766 Rope: 1/2" / 12 and 14mm
- B612C-6** Barracuda Stainless S. w/capstan. Chain: 6mm DIN766 Rope: 12 and 14mm
- B612C-7** Barracuda Stainless S. w/capstan. Chain: 1/4"HT G43 / 7mm DIN766 Rope: 1/2" / 12 and 14mm

Motor: 650w 12v

Speed Down: 36m / 119ft min

Speed Up: With normal load 6mm chain approx 22m / 72ft min. Rope/chain combo: approx 30m / 99ft min.

Amp draw down: 25amp

Amp draw up: With normal load 6mm chain approx 45amp. Rope/chain combo. approx 35amp.

Most used chain lenght 6mm: 30 to 50m.

Most used rope chain combos: DB1/4-150 165ft / 50m, DB1/4-200 215ft / 65m.

Anchors: 5kg / 11lbs to 8kg / 17,6lbs

Circuit breaker: 80amp (90080)

Cable size: 16mm² / 5AWG (Normal cable lenght)

Switch gear: Toggle switch 90800, Rocker switch panel 90801, Footswitch 90900, Radio remote 91354, Combo switch pack 92080.

Deck thickness: 20mm to 35mm / 3/4" to 1,5" (Up to 65mm - 2,5" with longer bolts)