

# ANCHORLIFT<sup>®</sup>

WORLD CLASS WINDLASS SYSTEM

**HIGHSPEED**  
WINDLASS

## Barracuda 900

---

Boats from 25ft to 35ft up to 4500kg / 9900Lbs.



**Model No:**

- BA912-6** Barracuda Aluminium Low profile. Chain: 6mm DIN766 Rope: 12 and 14mm
- BA912-7** Barracuda Aluminium Low profile. Chain: 1/4"HT G43, 7mm DIN766 Rope: 1/2", 12 and 14mm
- BA912C-6** Barracuda Aluminium w/capstan. Chain: 6mm DIN766 Rope: 12 and 14mm
- BA912C-7** Barracuda Aluminium w/capstan. Chain: 1/4"HT G43, 7mm DIN766 Rope: 1/2", 12 and 14mm
- B912-6** Barracuda Stainless S. Low profile. Chain: 6mm DIN766 Rope: 12 and 14mm
- B912-7** Barracuda Stainless S. Low profile. Chain: 1/4"HT G43 / 7mm DIN766 Rope: 1/2" / 12 and 14mm
- B912C-6** Barracuda Stainless S. w/capstan. Chain: 6mm DIN766 Rope: 12 and 14mm
- B912C-7** Barracuda Stainless S. w/capstan. Chain: 1/4"HT G43 / 7mm DIN766 Rope: 1/2" / 12 and 14mm

**Motor:** 900w 12v

**Speed Down:** Approx 38m / 126ft min

**Speed Up:** With normal load 6mm chain approx 25m / 83ft min. Rope/chain combo: approx 33m / 109 ft min.

**Amp draw down:** 25amp

**Amp draw up:** With normal load 6mm chain approx 47amp. Rope/chain combo. approx 38amp.

**Most used chain lenght 6mm:** 30 to 50m.

**Most used rope chain combos:**

DB1/4-150 165ft / 50m, DB1/4-200 215ft / 65m, DB1/4-250 / 265ft / 80m

**Anchors:** 8kg / 17,6lbs to 10kg / 22lbs

**Circuit breaker:** 100amp (Partno.90100)

**Cable size:** 25mm<sup>2</sup> / 3AWG (Normal cable lenght)

**Switch gear:** Toggle switch 90800, Rocker switch panel 90801, Footswitch 90900, Radio remote 91354, Combo switch pack 92100.

**Deck thickness:** 20mm to 35mm / 3/4" to 1,5" (Up to 65mm - 2,5" with longer bolts)